WO 2005/052986 PCT/IB2004/052369

PHNL031400 PCT/IB2004/052369

13

CLAIMS:

5

10

15

1. An electric lamp comprising a light-transmitting lamp vessel (1; 11) in which a light source (2; 12) is arranged,

said electric lamp comprising a light-absorbing medium (6; 16) exhibiting a spectral transition in the visible range,

- the spectral transmission T of light transmitted by the light-absorbing medium (6; 16) changes from T \leq 0.15 to T \geq 0.75 in a wavelength range having a width $\lambda \leq$ 75 nm, at least a part of the lamp vessel (1; 11) being provided with an interference film (5; 15), characterized in that the maximum reflection R_{max} of the interference film (5; 15) lies in the range from $0.50 \leq R_{max} \leq 0.90$ and in that the variation in the reflection R of the interference film (5; 15) in the wavelength range from $400 \leq \lambda \leq 690$ nm ranges from 0.0 to R_{max} .
- 2. An electric lamp as claimed in claim 1, characterized in that the variation in the reflection R of the interference film (5; 15) in the wavelength range from 400 $\leq \lambda \leq$ 690 nm ranges from 0.2 to R_{max}.
- 3. An electric lamp as claimed in claim 1 or 2, characterized in that a wall of the lamp vessel (1) comprises the light-absorbing medium.
- 4. An electric lamp as claimed in claim 1 or 2, characterized in that the light-absorbing medium (6; 16) comprises a light-absorbing coating which is situated between the lamp vessel (11) and the interference film (15).
- 5. An electric lamp as claimed in claim 1 or 2, characterized in that the electric lamp emits colored light, in operation, and has an at least substantially color-neutral appearance in the off state.
 - 6. An electric lamp as claimed in claim 1 or 2, characterized in that the light-absorbing medium (6; 16) comprises an amber-colored or red-colored transmission.

WO 2005/052986 PCT/IB2004/052369

PHNL031400

PCT/IB2004/052369

14

7. An electric lamp as claimed in claim 1 or 2, characterized in that the interference film (5; 15) comprises layers of alternately a first layer of a material having a comparatively high refractive index and a second layer of a material having a comparatively low refractive index.

5

8. An electric lamp as claimed in claim 7, characterized in that the second layer of the interference film (5; 15) comprises predominantly silicon oxide, and in that the first layer of the interference film (5) predominantly comprises a material whose refractive index is high in comparison with a refractive index of silicon oxide.

10

9. An electric lamp as claimed in claim 7, characterized in that the first layer of the interference film (5; 15) comprises a material selected from the group formed by titanium oxide, tantalum oxide, zirconium oxide, niobium oxide, hafnium oxide, silicon nitride and combinations of said materials.

15

- 10. An electric lamp as claimed in claim 7, characterized in that the first layer of the interference film (5; 15) comprises a material selected from the group formed by titanium oxide and niobium oxide.
- 20 11. An electric lamp as claimed in claim 7, characterized in that the interference film comprises 3-5 layers.
 - 12. An electric lamp as claimed in claim 7, characterized in that the interference film comprises 3 layers.